

US 15C Series

Data Collection Terminal

Choice of Proximity, Barcode, Magnetic Stripe of Fingerprint Reader in a compact design

US 15C Series Features





✓ Hardware level clock authentication

Support for local and external data/system backup

✓ User level duplicate punch prevention

Tip entry support

Multiple level job code support

Customizable user access control privileges

Enhanced network security

Web server support as a standard function

Automatic status key switch

✓ Self-Service API





9 Digits User Id

Customizable bell schedules

Private or public SMS messaging support

USB-host

User Attendance search

PUSH and Standalone SDK combatibility with TFT 2.0

Enhanced encryption system for data integrity and security

Hardware Specifications

Capacity

Cards: 10,000

Transactions: 100,000 Finger templates: 3,000

Communication

RS232, Ethernet, USB-Host, WiFi

Display

3" Color TFT LCD screen

Environment

Operating Temperature: 32°F -113°F (0°C- 45°C)

Operating Humidity: 5% - 80%

Power

12V DC, 1.5A

Optional: 12 V POE injector (sold separately)
Optional: 12V Battery Backup (sold separately)

Supported Options

US15C-1D: Fingerprint and standard RFID prox reader

US15C-HID: Fingerprint and HID prox reader

US15C-MAG: Magnetic card reader US15C-B: Barcode card reader US15CR Standard: RFID prox reader

S15CR-HID: Standard HID prox reader

Dimension

6.5 in x 5.5 in x 1.8 in (16.5 cm x 14 cm x 4.6 cm)

Weight: 0.95 lb (0.43kg)



Get in touch

Our team of Workforce Management Specialists are ready to help you save both time and money through automated scheduling and time & attendance software solutions.